

Specifications for imageRUNNER 1024F



Standard Type	Monochrome Laser MFP (P / C / S / F), Auto Duplex Print	
CPU (Processor)	192MHz	
System Memory (On Board)	128MB	
Interface	Standard:	USB 2.0
	Optional:	Ethernet 100 BaseTX / 10 BaseT
Copy		
Type	Monochrome Laser	
Copy Speed	24cpm / A4	
Copy Resolution	600 x 600dpi	
Halftones	256 level	
First Copy Time	< 8secs.	
Multiple Copies	1 to 99	
Duplex Function	Yes with Duplex Scanning (1:2, 2:2, 2:1)	
Reduction	50%, 70%, 81%, 86%	
Enlargement	115%, 122%, 141%, 200%	
Zoom	50% ~ 200%	
Copy Size	Up to LGL (via Platen & ADF)	
Toner Save Mode	On / Off	

Copy Features	ID Card Copy (by setting), Memory Sort, Toner Save mode, 2-on-1 combination
Copy Memory	128MB (Share)
Warm-Up Time	< 16secs.
Print	
Printing Method	On-Demand Fixing (SURF)
PDL	UFR II LT (PCL5e / 6 option)
FPOT (A4)	< 8secs.
Print Speed	Up to 24ppm (A4)
Print Resolution (optical)	600 x 600dpi
Print Resolution (enhanced)	1200 x 600dpi
Duplex Function	Yes (A4 / LTR / LGL)
Print Memory	128MB (Share)
Toner Save Mode	On / Off
Others	Canon Page Composer, BarDIMM (Bar Code Printing On / Off), (PCL Kit is required for BarDIMM)
Network Print	Canon NIC (option)
OS Supported (UFR II Lt)	Win, Mac, Linux
Color Scan	
Local Scan / PULL-SCAN (from Software)	
Software	iR Toolbox, ScanGear driver
Scanning Method	Colour CIS
Colour mode	Colour, B&W & Greyscale
iR Toolbox Scan function	Scan to Email / PDF / File / Applications
Scanning Resolution	600 x 600dpi (optical), 9600 x 9600dpi (interpolated)
Colour Depth	24 bit
Document Size	Up to LGL
Multipage Scanning / File	Duplex ADF / PDF
Duplex Scanning	Yes (via DADF)
Compatibility	TWAIN, WIA (XP & Vista only)
File Format	JPEG, PDF, TIFF, BMP
USB Connectivity	Standard (Local)

OS Supported	Win
Network Scan / PUSH-SCAN	
Software	N/A
Network Destinations	N/A
Colour mode	N/A
File Format	N/A
Fax	
Applicable Line	PSTN
Modem Speed	33.6Kbps, Super-G3 (approx. 3secs. / page)
Fax Resolution	Standard, Fine / Photo, Super Fine, Ultra Fine
Image Processing System	UHQ™ (Ultra High Quality)
Fax Memory Capacity	256 pages
Fax Speed Dial	23 one-touch, 177 coded dials, 199 group dials
Sequential Broadcasting	201 Locations
Address Book Capacity	200 Locations
Address Book Utilisation	Fax speed dial destinations
Compression Mode	MH, MR, MMR, JBIG
Receive Mode	FAX Only, Manual, Answering DRPD, Fax / Tel Auto SW, Net Switch
ECM (Error Correction Mode)	Yes (RX / TX)
PC-Fax	Yes
SEND / iFax	N/A
Remote Reception	Yes (Default ID: 25)
Delayed Transmission	Yes (64 locations)
Memory Lock Reception	Yes
Favourite Buttons	N/A
Auto Double-sided Fax Printing	Yes
Auto Double-sided Fax Sending	Yes
Auto Receive Reduction	Yes (75 - 100%)
Report Settings	Rx / Tx / Report with Tx Image / Print Error Only, Report List, Tx / Rx in Separate page, Activity (Manual / Auto, Up to 40 transactions / page),
Image Data Backup	1 hour (JBIG)

Paper Handling		
Paper Feeding	500 sheets cassette 100 sheets Bypass tray	
Optional Paper Cassette	500 sheets	
Paper Weight	64 ~ 90g/m ² (cassette) 56 - 128g/m ² (Bypass tray)	
Paper Output	100 sheets	
Auto Document Feeder	50 sheets (Duplex ADF)	
Paper Size	A4 / LTR / LGL (cassette) Envelopes, A5-A4, LTR, LGL (MP Tray)	
Interface / Software		
Standard Port	USB 2.0 High Speed	
OS Compatibility (UFR II Lt)	Windows 2000, XP, 2003 Server, VISTA, Server 2008, MAC OSX*1*2 Linux OS various version (available at later time)	
OS Compatibility (PCL5e / 6 optional)	Windows 2000, XP, 2003 Server, VISTA, Server 2008	
Networking		
Network built-in	No (Option)	
Network Interface	Canon Network Card (Ethernet 10 Base T / 100 Base TX)	
Network Print	Optional	
Network PC Fax	Optional	
Network Scan	N/A	
IP Environment	IPV4.0	
OS Supported functions	Win:	Print, PC-Fax (inc. network)
	Mac:	Print, PC Fax (inc. network)
	Linux:	Print (inc. network)
Management Utility		
ID Management	Up to 1000 User IDs	
Canon Management Solutions Compatibility	imageWARE Accounting Manager, imageWARE Publishing Manager, imageWARE Management Console, e-Maintenance.	

General Specification		
Power Consumption	Sleep:	Approx. 5.9w
	Standby:	Approx.15.6w
	Max.:	954W
Energy Star	Yes	
Power Source	AC 220 - 240V, 50 - 60Hz	
Acoustic Noise Level	Standby:	Approx. 30db(A) max.
	Copy:	under 56db(A) max.
Recommended Print Volume	3000 - 7800 pages per month	
Dimensions (Main Unit + Doc Feeder)	520 x 457 x 453mm	
Weight (Main Unit without CRG)	Approx. 24.1kg	
Consumables		
Toner Cartridge	Type:	Toner & Drum separate
	Model:	Toner: NPG-32 ; Drum: NPG-32
	Yield (A4)* ³ :	Toner: 7,800 pages* ³ , Drum: 26,000 pages* ³
Optional Accessories		
Cassette Feeding Unit	Model:	Module - N2
	Capacity / Media:	500 sheets capacity (A4 / LTR / LGL, 64 - 90g/m ²)
Card Reader-E1	Dimension:	88 x 100 x 32mm
	Weight:	295g
	Attachment Kit:	Card Reader Attachment-D2
PCL Printer Kit	AB1	
Network Kit	Canon Network Card	

Specifications are subjected to change without notice. :

*¹ Driver for Mac OS X is not bundled with product.

*² Support Mac OS 10.2.8 ~.

*³ Declared yield value in accordance with ISO / IEC 19752.



- **Address** : Office No. D-4, Ambika Darshan Building, Chittabhai Patel Road, Behind Sapan Nikhil Classes, Ahead of Kandivali Bus Depot, Kandivali (E), Mumbai-400101.
- **Phone No**: +022-28460505 (50 lines)
- **Email**: itsolutions@varay.co.in