

Specifications for imageRUNNER ADVANCE C5235



Type	Reader, Printer Separated, Desktop	
Maximum Original Size	A3	
Copy Sizes	Cassette:	305 x 457mm, A3, A4, A4R, A5R, B4, B5, B5R Custom Size 139.7 x 182mm to 304.8 x 457.2mm Optional Envelope Feeder, No.10 (COM10), Monarch, DL, ISO-C5
	Stack Bypass:	A5R - SRA3 (320 x 450mm), Envelopes Custom Size 99 x 140mm to 320 x 457mm
Resolution	Reading:	600 x 600dpi
	Copying:	600 x 600dpi
	Printing:	1200 x 1200dpi (text / line only)
Copy / Print Speed	A4 (B&W / Colour):	35 / 30ppm
	A3 (B&W / Colour):	20 / 18ppm
Magnification	Zoom:	25 - 400%
First Copy Time	Black-and-White:	5.4secs.

	Full Colour:	8.1secs.
Warm-Up Time	31 seconds	
Multiple Copies / Prints	1 to 999 sheets	
Duplexing	Standard automatic stackless	
Paper Weight	Cassette:	52 to 220gsm
	Stack Bypass:	52 to 256gsm
Paper Capacity	Standard:	550 sheets x 2 cassettes (80gsm) Stack Bypass: 100 sheets (80gsm)
	Optional:	550 sheets x 2 cassettes (80gsm)
	Paper Deck:	2,700 sheets (80gsm)
	Total capacity:	5,000 sheets
CPU	1.66GHz	
Memory	Standard:	2GB RAM
	Maximum:	2.5GB RAM
Hard Disk Drive	Standard:	160GB (Available Disk Space: 15GB)
	Maximum:	1TB (Available Disk Space: 629GB)
Interface Ethernet	(1000BaseT / 100Base-TX / 10Base-T)	
Power Supply	220-240V AC, 50 / 60Hz	
Power Consumption	1.8kW max. (C5255 / C5250), 1.3kW max. (C5240 / C5235)	
Dimensions (H x W x D)	Only the Main Unit:	800 x 620 x 700mm
	With the Duplex Colour Image Reader Unit-E1:	950 x 620 x 715mm
	With the Colour Image Reader Unit-F1:	931 x 620 x 712mm
	With the Colour Image Reader Unit-F2:	831 x 620 x 700mm
Weight	Only the Main Unit:	Approximately 139kg
	With the Duplex Colour Image Reader Unit-E1:	Approximately 153kg

	With the Colour Image Reader Unit-F1:	Approximately 148kg
	With the Colour Image Reader Unit-F2:	Approximately 144kg
Print Specification		
PDL	UFR II (Standard), PCL 5c/6 (Optional), Adobe PostScript 3 (Optional)	
Resolution	1200 x 1200dpi (Text / Line only), 600 x 600dpi	
Memory	2GB (Uses Main unit RAM)	
Hard Disk	Standard 160GB (Available Disk Space: 15GB)	
CPU	Canon Custom Processor, 1.2GHz (Uses Main unit CPU)	
Supported OS	PCL:	Windows 2000 / XP / Server2003 / Vista / Server2008 / Win7
	Adobe PostScript 3:	Windows 2000 / XP / Server2003 / Vista / Server2008 / Win7, MacOSX (10.4.9 or later)
UFR II	Windows 2000 / XP / Server2003 / Vista / Server2008 / Win7 / Linux, Mac OSX (10.4.9 or later)	
Mac-PPD	Mac OS 9.1 or later, Mac OSX (10.2.8 or later)	
Interface	Ethernet (1000Base-T / 100Base-TX / 10Base-T), USB2.0	
Network Protocol	TCP / IP (LPD / Port9100 / WSD / IPP / IPPS / SMB / FTP), IPv6, IPX / SPX (NDS, Bindery), AppleTalk	
Pull Scan	Network TWAIN Driver (75 to 600dpi 24 bits colour / 8 bits grayscale / 2 bits Black & White)	
Send Specification (Standard)		
Scan Resolution	100 x 100dpi, 150 x 150dpi, 200 x 100dpi, 200 x 200dpi, 200 x 400dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi	
Destinations	E-Mail / Internet FAX (SMTP), PC (SMB, FTP), iWDM, WebDAV	
Address Book	LDAP, Local (Max.1800)	
File Format	TIFF, JPEG, PDF, XPS, High compression PDF / XPS, PDF / A-1b, Optimize PDF for Web	



- **Address** : Office No. D-4, Ambika Darshan Building, Chittabhai Patel Road, Behind Sapan Nikhil Classes, Ahead of Kandivali Bus Depot, Kandivali (E), Mumbai-400101.
- **Phone No**: +022-28460505 (50 lines)
- **Email**: itsolutions@varay.co.in