Specifications for imageCLASS LBP7100Cn



Print			
Printing Method	Colour Laser Beam Printing		
Fixing Method	On Demand Fixing		
Print Speed	Mono:	14ppm (A4/Letter)	
	Colour:	14ppm (A4/Letter)	
Print Resolution	600 x 600dpi		
	9600 (equivalent) x 600dpi		
	1200 x 1200dpi (equivalent)		
First Printout Time (FPOT)	18/18 secs. (A4 / Letter)		
Warm-up Time (from Power On)	20secs. or less		
Recovery Time (from Deep Sleep)	Approx. 4secs.		
Print Language	UFR II LT		
Paper Handling			
Paper Input (based on 80g/m ²)	150 sheets		
Paper Output (based on 80g/m ²)	125 sheets (Face-Down)		
Paper Size	A4 / B5 / A5 / Letter / Legal* / Executive / 16K / Foolscap / Statement / Envelope COM-10 / Envelope Monarch /		

	Envelope C5 / Envelope DL / 3x5 index card / Custom (Width: 83 ~ 215.9mm x Length: 127.0 ~ 355.6mm) * Legal refers to paper measuring 215.9 x 355.6mm (8.5 x14 inches)		
Paper Weight	60~220g/m ²		
Print Margins	5mm-top, bottom, left and right (Envelope: 10mm)		
Connectivity and Software			
Standard Interfaces (Wired)	USB 2.0 High Speed; 10Base-T / 100Base-TX		
Compatible Operating Systems	Windows:	Windows XP (32bit / 64bit) / Windows Server 2003 (32bit / 64bit) / Windows Vista (32bit / 64bit) / Windows Server 2008 (32bit / 64bit) / Windows Server 2008 R2 (64bit) / Windows 7 (32bit / 64bit)	
	Macintosh:	Mac OS 10.6 and above *1	
	Linux		
	Citrix		
General Specifications			
Operation Panel	3 Keys, 11 LEDs		
Device Memory	64MB		
Noise Level* ³	During Operation:	6.52B or less (Sound Power) Approx. 49dB (Sound Pressure)	
	During Standby:	Inaudible (Sound Power)* ⁴ Inaudible (Sound Pressure)* ⁴	
Power Consumption	Maximum:	800W or less	
	During Operation:	Approx. 340W	
	During Standby:	Approx. 10W	
	During Sleep:	Approx. 0.9W	
Energy Star TEC (Typical Electricity Consumption)	0.4 kWh/week		
Dimensions (Width x Depth x Height)	406 x 454 x 255mm (Excluding protrusion)		
Weight (without Cartridge)	Approx. 16.6kg		
Power Requirements	220-240V (±10%), 50	220-240V (±10%), 50/60Hz (±2Hz)	
Operating Environment	Temperature:	10 ~ 30°C	

	Humidity:	20 ~ 80%RH (No Condensation)
Toner Cartridge* ⁵	Cartridge 331 Black:	1,400 pages (Bundled Cartridge: 800 pages)
	Cartridge 331 II Black:	2,400 pages
	Cartridge 331 CMY:	1,500 pages (Bundled Cartridge: 800 pages)
Monthly Duty Cycle*6	30,000 pages	
Recommended Monthly Print Volume	200 - 1,000 pages	

Specifications are subject to change without notice. :

- *1 The latest drivers for Mac OS can be downloaded from www.canon-asia.com when available.
- *2 The latest drivers for Linux can be downloaded from www.canon-asia.com when available.
- *3 Tested in accordance to ISO7779 and declared per ISO9296.
- *4 "Inaudible" means each sound pressure level at bystander's position is less than the absolute criterion value (about background noise) of ISO 7779.
- *⁵ Toner cartridge yield in accordance with ISO/IEC 19798.
- *6 Monthly Duty Cycle value provides a means for comparison of product robustness in relation to other Canon Laser Devices, and does not refer to actual maximum image output per month.



- Address: Office No. D-4, Ambika Darshan Building, Chittabhai Patel Road, Behind Sapan Nikhil Classes, Ahead of Kandivali Bus Depot, Kandivali (E), Mumbai-400101.
- Phone No: +022-28460505 (50 lines)
- Email: itsolutions@varay.co.in