Specifications Benq MX726



Benq MX726 specifications

Projection System	DLP
Native Resolution	XGA (1024x768)
Brightness*	4,000 ANSI Lumen
Contrast Ratio	11,000:1
Display Color	1.07 Billion Colors
Lens	F=2.59~2.91, f=16.87~21.87mm
Aspect Ratio	Native 4:3 (5 aspect ratio selectable)
Throw Ratio	1.5 - 1.97 (65" ±3% @2m)
Image Size (Diagonal)	50" ~ 300"
Zoom Ratio	1.3x
Lamp Type	280W
Lamp(Normal/Economic	3000/4000/6000 hours

Mode/SmartEco Mode)*	
Keystone Adjustment	2D, Vertical & Horizontal ± 30 degrees
Projection Offset	Vertical: 128% ±5%
Resolution Support	VGA (640 x 480) to WUXGA_RB(1920 x 1200) *RB =
**	Reduced blanking
Horizontal Frequency	15K-102KHz
Vertical Scan Rate	23-120Hz
Interface	Computer in (D-sub 15pin)x 2 HDMIx2 (HDMI with MHL2.0 x1,HDMI x 1) MHLx 1 (HDMI with MHL2.0) Monitor outx 1 Composite Video in (RCA)x 1 S-Video inx 1 Audio in (Mini Jack)x 1 Audio in (L/R)x1 Audio out (Mini Jack)x 1 Microphone in(Mini jack)x 1 Microphone in(Mini jack)x 1 Speaker 10W x 1 LAN(RJ-45) x 1 (LAN Control & LAN display) USB (Type A) x 1 USB (Type Mini B) x 1 DC 12V Trigger (3.5mm Jack) x 1 RS232 (DB-9pin) x 1 IR Receiver x2 (Front+Rear)
Dimensions(W x H x D)	314.2x116x216.3mm (include feet) 314.2x102x216.3mm (exclude)
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM
Weight	3.3 Kg (7.28 lbs)
Audible Noise	37/34 dBA (Normal/Economic mode)
Power Supply	AC100 to 240 V, 50 to 60 Hz
Power Consumption	Normal 270W, Eco 220W, Network standby <6.0W, Standby <0.5W
On-Screen Display Languages	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages)
Picture Modes	Dynamic / Presentation / sRGB / Cinema / (3D) / User 1 / User 2

Accessories (Included)	Carry bag Power Cord (by region) Remote Control w Battery VGA cable User Manual CD Quick Start Guide Lens Cover Warranty Card (by region)
Accessories (Optional)	Spare Lamp Kit Ceiling mount kit Carry bag 3D Glasses
3D Support and Compatibility	Frame Sequential: Up to 60Hz 720p Frame Packing: Up to 24 Hz 1080p Side by Side: Up to 24Hz 1080p Top Bottom: Up to 60Hz 1080p

^{*}Lamp life results will vary depending on environmental conditions and usage.
Actual product's features and specifications are subject to change without notice.



• Address: Office No. D-4, Ambika Darshan Building, Chittabhai Patel Road, Behind Sapan Nikhil Classes, Ahead of Kandivali Bus Depot, Kandivali (E), Mumbai-400101.

• Phone No: +022-28460505 (50 lines)

• Email: itsolutions@varay.co.in